



# Braille Battery™ MICRO-LiTE™ Lithium Technology

Lighter. Stronger. Faster.

Model Number: B128L-M6  
Battery Name: Braille MICRO-LiTE B128L-M6 Lithium Technology Racing Battery



**MICRO-LiTE  
LITHIUM**

- NEW FOR 2016: MORE CRANKING POWER, LOWER IMPEDANCE DESIGN
- Easy Install: Built in a Direct Replacement Size
- Safe: Sealed Safe Design, Proven Performance
- Fast Power: Rapid Recharge, Stable Voltage Output
- Greener: Modular Design For Longer Life
- Exclusive Braille Lithium Racing Warranty



## PHYSICAL SPECS

BCI Group: Same Length as Group 24, 27 & 34  
 Length: 10.0" / 254 mm  
 Width: 3.25" / 82.5 mm  
 Height: 6.00" / 152.4 mm  
 Minimum Weight: 8.3 lbs / 3.76 kg  
 Post Type: M6 Stud

Recommended Mount: Secure Mounting with  
 Vibration padding.  
 Braille #211 Optional

## PERFORMANCE

Voltage : 12 volts  
 Full Charge Range: 13.6 - 13.8 volts  
 Cranking Amps : 1698  
 Lead-Acid Equivalent Capacity: 90 Lithium AH (LAH)  
 Nominal Capacity (C/20 rate): 30 AH  
 Impedance: < 4.0 milliohms  
 Life Cycle @ 10% DOD: Up to 5000 cycles  
 Life Cycle @ 80% DOD: Up to 2000 cycles

## CHARGING & USAGE INFORMATION

Alternator: Automotive Compatible  
 Battery charger: Model # 12310L & 12325L  
 Rapid Recharge: 25 AH electronically controlled  
 Recommended Charge Voltage: 14.4 - 14.8 Volts  
 Do Not Exceed Charge Voltage: Up to 15 Volts  
 Minimum Recommended Voltage: 8.0 Volts

## WARRANTY

Warranty: 1 Year Free repair/replacement. See warranty terms and conditions.



\*Performance specifications denote maximum lead-acid equivalents. Actual performance may vary. Pricing, specifications and features current as of 1/16, subject to change without notice. For latest information, contact Braille directly.