



Engineered To Perform
hi-tecoils.com.au



FIRST CHOICE FOR OILS

Hi-Tec Oils is an Australian owned company with more than 200 years of lubricant technical expertise in its workforce. It is one of Australia's largest independent oil manufacturers, with warehouses in all Australian states and territories well as New Zealand.

Hi-Tec's range of motor cycle lubricants includes two and four stroke engine oils, gear oils, and fork oils as well as brake fluids, batteries and cleaning products. Its new 4 stroke motorcycle engine oil range includes mineral, semi-synthetic, synthetic and (for the purists) PAO ester based oils. The updated additive system provides for superior engine, clutch and gearbox protection in wet clutch applications (where the gearbox and engine are combined). These four stroke engine lubricants all meet the JASO MA/MA2 and API SN performance requirements and are suitable for use in on and off road bikes, dirt and enduro bikes, ATVs and quadbikes and scooters.

The Hi-Tec motor cycle range of products are suitable for equipment manufactured by major European, Asian and American OEMs.

FAST4 FOUR STROKE MOTORCYCLE OIL RANGE



FAST 4 100% PAO ESTER

Hi-Tec Fast 4 100% PAO Ester motorcycle oils are premium four stroke engine oils specially designed for racing and competition motorcycle applications including those with wet clutches. The use of PAO and ester base oils gives improved film strength, shear stability and heat resistance in the lubricant, allowing for longer running and higher temperature performance. The API SN rating provides for superior protection from wear, piston deposits and sludge; and the JASO MA2 rating provides for the correct clutch frictional characteristics with respect to DFI, SFI and STI.

Available in SAE: 5W40, 10W30, 10W40, 10W50, 10W60

Specification: JASO MA2/MA; API; SN, SM, SL, CF

Product Sizes: 1L, 4L, 20L, 200L

Product Code: HI1-2141, HI1-2153, HI1-2142,

HI1-2154, HI1-2144



FAST4 FULL SYNTHETIC

Hi-Tec Fast 4 MA2 Full Synthetic motorcycle oils are full synthetic oil based four stroke engine oils specially designed for use in motorcycles with wet clutches, exceeding the JASO MA2 and API SN specification requirements. They provide long life, cleanliness and reliability for the engine and the correct frictional characteristics for the clutch with respect to DFI, SFI and STI.

Available in SAE: 5W40, 10W40

Specification: JASO MA2/MA; API: SN, SM, SL, CF

Product Sizes: 1L, 4L, 20L, 200L

Product Code: HI1-2150, HI1-2149



FAST 4 SEMI SYNTHETIC

Hi-Tec Fast Semi Synthetic motorcycle oils are semi synthetic oil based four stroke engine oils specially designed for use in motorcycles with wet clutches, exceeding the JASO MA2 and API SN specification requirements. They provide long life, cleanliness and reliability for the engine and the correct frictional characteristics for the clutch with respect to DFI. SFI and STI.

Available in SAE: 10W30, 10W40, 10W50, 20W50

Specification: JASO MA2/MA; API: SN, SM, SL, CF

Product Sizes: 1L, 4L, 20L, 200L

Product Code: HI1-2145, HI1-2146, HI1-2147, HI1-2148



FAST4 MINERAL

Hi-Tec Fast 4 MA2 motorcycle oils are mineral oil based four stroke engine oils specially designed for use in motorcycles with wet clutches, exceeding the JASO MA2 and API SN specification requirements. They provide long life, cleanliness and reliability for the engine and the correct frictional characteristics for the clutch with respect to DFI, SFI and STI.

Available in SAE: 10W30, 10W40, 15W40, 20W40

Specification: JASO MA2/MA; API: SN, SM, SL, CF

Product Sizes: 1L, 4L, 20L, 200L

Product Code: HI1-2083, HI1-2082B, HI1-2048C, HI1-2151

FAST2 TWO STROKE MOTORCYCLE OIL RANGE



HI-TEC OILS FAST MOTORCYCLE OILS

FAST 2 HIGH PERFORMANCE

Hi-Tec Fast 2 High Performance 2 Stroke motorcycle oil is a mineral oil based two stroke motor cycle engine oil formulated with self-mixing solvents and detergent additives to create a modern low ash lubricant. It provides for excellent engine cleanliness, low smoke emissions and freedom from ring sticking. It should be used at the fuel/oil ratio recommended by the engine manufacturer.

Specification: API TC, JASO FA and FB, ISO-L-EGB

Product Sizes: 1L (HI8-2135A-0001) and 4L (HI8-2135A-0004)



FAST2 FULL SYNTHETIC

Hi-Tec Fast 2 Full Synthetic 2 Stroke motorcycle oil is a full synthetic two stroke motor cycle engine oil formulated with self-mixing solvents and detergent, dispersant and lubricity additives to create a modern low ash, low smoke lubricant. It provides for excellent engine cleanliness, low smoke emissions and freedom from ring sticking. It should be used at the fuel/oil ratio recommended by the engine manufacturer.

Specification: API TC ISO-L-EGB, -EGC and -EGD JASO FA, FB, FC and FD

TISI requirements for Detergency and Lubricity Piaggio Hexagon

Product Sizes:1L (HI8-2134A-0001), 4L (HI8-2134A-0004), 5L (HI8-2134A-0005), 20L (HI8-2134A-0020), and Bulk (HI8-2134A-BULK)



HTO BIKEWASH

Hi-Tec BIKEWASH is a biodegradable, coconut oil based detergent formulation containing inorganic phosphates for the purpose of removing dirt, mud, oil film and road grime from all washable motorcycle surfaces.

Manual washing - Dilute with up to 10 parts of clean water, sponge on, allow 3-5 minutes, and then rinse clean with water.

Product Size: 1L HI8-3167



HTO FORK OILS



FORK OILS are a premium motorcycle suspension fluids suitable for conventional, upside down and cartridge forks, dampers and rear shock absorbers. Their high shear stability provides improved suspension control over a wide temperature range in competition, off road and on road conditions. They are safe for use with steel, aluminium and other alloys.

Available in: 1L Fork 0il 5 (HI5-2739B-0001)

1L **Fork Oil 10** (HI5-2741B-0001) 1L **Fork Oil 15** (HI5-2742B-0001)

1L Fork Oil 20 (HI5-2744B-0001)



HTO GEAR OIL 10W/40

GEAR OIL 10W40 GL-4 gear lubricant is specifically recommended for motorcycle transmissions where the engine oil and gear box oil are in separate compartments. It is specially designed to provide improved oil seal life, increased durability (gear surface life) and better corrosion protection for yellow metals under both wet and dry conditions, thereby ensuring a long service life. Meets API GL-4.

Available in SAE: 10W40

Specification: API GL-4

Product Sizes: 1L (HI4-2425B-0001)



HTO FOAM AIR FILTER OIL

Hi-Tec Foam Air Filter Oil is an advanced low viscosity coating treatment designed to improve the efficiency of foam air filters used on 2 stroke and 4 stroke motorbikes.

- Prevents particles and water from entering the engine
 Blue colour shows that even cover has been achieved
- Non hazardous solvent-free formula will not damage the foam filter construction
- Ideal for off road bikes and quads.

Product Sizes: 500mL (HI1-2143)



HTO BRAKE FUID

Hi-Tec Super DOT 4 Brake Fluid is a premium quality high boiling point brake fluid that meets the requirements of the DOT 4 Class 4 specification.

- Equilibrium Reflux Boiling Point is greater than 280°C
- Wet Equilibrium Reflux Boiling Point is greater than 180°C
- · High heat stability.
- · Lubricates moving parts to prolong service life.
- Protects metal brake system parts from corrosion both ferrous and non ferrous.
- Gently swells rubber seals to enhance sealing & prevent system leaks.
- Good low temperature performance.
- Flows smoothly in hot or cold conditions, sealing & preventing system leaks.

Specification: DOT 4 Class 4

Product Sizes: 500mL (HI8-3146-00005) and 20L



HI-TEC OILS FAST MOTORCYCLE OILS

AGM FACTORY SEALED

| Product Code | PTX7LBS-FS |
|-----------------|----------------------|
| Replaces | GTX7L-BS, YTX7LBS-BS |
| 12 Volt | 90cca |
| Dimensions | 114 x 71 x 131 |
| Terminal layout | |

Also available PTX4LBS, PTX5LBS-FS, PTX7ABS-FS, PTX9BS-FS



AGM FACTORY SEALED

| Product Code | PTX12BS-FS |
|-----------------|----------------------------|
| Replaces | ETX12, YTX12BS, GTX12BS |
| 12 Volt | 200cca |
| Dimensions | 150 x 87 x 129 |
| Terminal layout | |

Also available PTX14BS-FS, PTX14AHBS-FS, PTX14AHLBS-FS



AGM FACTORY SEALED

| Product Code | PTX20HLBS-FS |
|-----------------|------------------|
| Replaces | ETX20L, YTX20LBS |
| 12 Volt | 310cca |
| Dimensions | 175 x 87 x 155 |
| Terminal layout | |

Also Available PTX20HBS-FS



AGM FACTORY SEALED

| Product Code | PTX19CLBS-FS |
|-----------------|----------------------------------|
| Replaces | ETX16L , PTX19CL-BS, CB16CL-B |
| 12 Volt | 280cca |
| Dimensions | 175 x 100 x 175 |
| Terminal layout | |

Other models available contact your sales representitive for more information



LITHIUM SUPER SPORT

| Product Code | SPLFP-7L |
|-----------------|--|
| Replaces | YTX4L-BS, YTX5L-BS, YTX7LBS, SLFP5ZS, |
| | SLFP7ZS |
| 12 Volt | 140 Cca |
| Dimensions | 107 x 56 x 85 |
| Terminal layout | |
| | |



LITHIUM SUPER SPORT

| Product Code | SPLFP-14BR |
|-----------------|--|
| Replaces | YT7B-BS, YT9B-BS, YTZ10S, YT12B-BS, SLFP12BS |
| 12 Volt | 280 Cca |
| Dimensions | 134 x 65 x 92 |
| Terminal layout | |



LITHIUM SUPER SPORT

| Product Code | SPLFP-20L |
|-----------------|----------------|
| Replaces | YTX20LBS, |
| | YTX20HLBS, |
| | YTX24HLBS, |
| | SLFP20HL-BS |
| 12 Volts | 360 Cca |
| Dimensions | 148 x 86 x 105 |
| Terminal layout | |



LITHIUM SUPER SPORT

| Product Code | SPLFP-30L |
|-----------------|----------------------------------|
| Replaces | PIX30HLBS-FS, ETX30L, YIX30L, |
| | YB30LB, SLFP30L, SLFP30HL |
| | SLIT SUIL |
| 12 Volt | 400 Cca |
| Dimensions | 165 x 86 x 130 |
| Terminal layout | |
| | |

Other models available contact your sales representitive for more information



www.hi-tecoils.com.au

Hi-Tec Oils (Head Office)

5 Tarlington Place Smithfield NSW 2164

Ph: 1300 796 009 | (02) 9616 5700

Fax: (02) 9604 1611





Ph: 0409 162 582

Hi-Tec Oils (Victoria) 1/ 41-45 Burns Road

Ph: (03) 9369 5512 Altona VIC 3018 Fax: (03) 9369 5682

Hi-Tec Oils (Queensland)

37 Nealdon Drive Ph: (07) 3200 3492 Meadowbrook QLD 4131 Fax: (07) 3200 7136

Hi-Tec Oils (Bohle Queensland)

Northern Logistics & Warehousing - Dealer

27-33 Toll Street

Bohle QLD 4818 Ph: (07) 4774 3507

Hi-Tec Oils (South Australia)

6-7/ 3A Newcastle Crescent Ph: (08) 8162 5807 Cavan SA 5094 Fax: (08) 8359 7849

Hi-Tec Oils (Western Australia)

1/ 46 Baile Road Ph: (08) 9256 4528 Canning Vale WA 6155 Fax: (08) 9455 2129

Hi-Tec Oils (Northern Territory)

15 Bishop Street (08) 8931 4857

Woolner NT 0820 Fax: (08) 8931 4981 Hi-Tec Oils (TAS Distributor) 125 Swanston Street

New Town TAS 7008 Ph: 1300 914 616

Hi-Tec Oils (ACT Distributor)

Ph: (02) 6232 9515 86 Bayldon Road Queanbeyan NSW 2620 Fax: (02) 6232 9511

Hi-Tec Oils (Newcastle)

1/4 Pennant Street Ph: (02) 4956 6000 Fax: (02) 4956 6888 Cardiff NSW 2285

Hi-Tec Oils (Port Lincoln)

Port Lincoln SA 5606

6 Freedman Street

Pine Freezers Road

Hi-Tec Oils (North Geelong) M & R Distributors - Dealer

North Geelong VIC 3215 Ph: (03) 5277 1107

Hi-Tec Oils (Wodonga)

North East Oil Distributors - Dealer

74 Church Street

Wodonga VIC 3690 Ph: (02) 6056 5055

Hi-Tec Oils (Tamworth)

Unit 3, 20 Crown Street

Taminda NSW 2340 Ph: 1300 796 009

Distributed by:

Quality Assurance Hi-Tec Oil Traders Pty Ltd has been assessed by QAS International and following: Manufacture of finished lubricants for automotive, commercial and industrial Should you require a copy of our Quality Assurance certificate please don't hesitate to ask

Hi-Tec Oils Oil Sampling - We offer clients an oil condition monitoring service. The benefits of





Althoughevery care is taken to ensure accuracy and completeness in compiling this data, no liability can be accepted by Hi-Tec Oils for damage or loss caused by any errors or omissions in the information given, directly or indirectly. Suitability of products referred to in this catalogue is the customers so live responsibility. Aways refer to technical data to confirm suitability which is available on request from Hi-Tec Oils.

HTO 1448 March 2021 v1